



## PI336GL PICO (CHROMEOS FLEX CERTIFIED) SKU: ZP-PI336GL













### **TECHNICAL SPECIFICATIONS**

- FEATURES

  ChromeOS Flex certified
  Passive Cooling Embedded Solution
  Ultra-small form factor: 115 x 76 x 26.7 (mm)
  Intel Celeron N6211 Dual core
  System-on-Chip with 1.5MB cache
  Dual Display Output: HDMI, DisplayPort
  Full network connectivity Gigabit Ethernet, Sparklan WiFi 5, Bluetooth 5
  Hardware watchdog timer:
  Timeout value = 1-65535 (min/sec)
  Durable Aluminum Enclosure
  Long Product Life Cycle

- PROCESSOR
   Intel Celeron N6211
  (Dual-core 1.2GHz up to 3.0GHz)
   1.5MB cache, 6.5W TDP

- GRAPHICS ENGINE

  Integrated Intel UHD Graphics

  HDMI 2.0: up to 4096x2160@60Hz

  DisplayPort 1.2: up to 4096x2160@60Hz

MEMORY
Onboard 4GB LPDDR4X memory

## **DISPLAY OUTPUT**• 1 × HDMI 2.0

- AUDIO INTERFACE

   8-channel digital audio via HDMI port

   3.5mm Stereo Headphone / Mic Combo jack

# POWER INPUT • DC 5V, 20W

### **OPERATING TEMPERATURE**

- SUPPORTED OS
  ChromeOS Flex (OS is not pre-loaded but FREE to download from Chrome Enterprise)
  Windows 11 / 10 / 10 IoT ENT LTSC
  Ubuntu 20.04.3 LTS Linux

- INSIDE THE BOX

   ZBOX PRO PI336GL pico

   Universal AC adapter

   Detachable AC plugs (EU, UK, US regions)

   CTIA to OMTP 3.5mm audio adapter converter

   2 x Wi-Fi Tri-band antenna























